

# LMB...UU..OP Series

LMB...UU	top devresi	Ağırlık (kg)	LMB...UU-AJ	top devresi	Ağırlık (kg)	Nominal mil ölçü			diğer										Ana boyutlar ve tolerans								eksantriklik		Temel yük devresi (kN)					
						İnc	mm	İnc	Hassaslık (µm)	Yüksek (İnc)	Yüksek (µm)	Dfinc/mm)	D Tolerans (µm)	D Tolerans (µm)	Lfinc/mm)	L Tolerans (İnc)	L Tolerans (µm)	Bfinc/mm)	B Tolerans (İnc)	B Tolerans (µm)	Wfinc/mm)	Dfinc/mm)	hfinc/mm)	hfinc/mm)	θ	Keskinlik	High	Radial beslek (Maks)	Dynamic Static					
LMB4	4	6	LMB4-AJ	4	1.5	—	—	1/8	6.35	0.25	6.35	0-0.0025	0/4	0-0.0060	0/9	5.00012.700	0-0.0045	0/11	7.500/19.050	0-0.008	0/200	0-0.008	0/200	0.030/0.092	4687/11.906	0/41	—	—	0.003/8	0.005/12	-0.001/3	206	265	
LMB8UU	4	14	LMB8UU-AJ	4	13.5	—	—	3/8	9.525	0.375	9.525	0-0.0025	0/4	0-0.0060	0/9	6.25015.875	0-0.0050	0/13	8.750/22.225	0-0.008	0/200	0-0.008	0/200	0.030/0.092	5880/14.935	0/41	—	—	0.003/8	0.005/12	-0.001/3	225	314	
LMB8UU	4	37	LMB8UU-AJ	4	36.5	LMB8UU-OP	3	28	1/2	12.7	0.5	12.7	0-0.0025	0/4	0-0.0060	0/9	8.750/22.225	0-0.0050	0/13	1.2500/1.750	0-0.008	0/200	0-0.008	0/200	0.030/0.092	8290/20.853	0/41.5	347/9375	80°	0.003/8	0.005/12	-0.001/3	510	784
LMB10UU	4	76	LMB10UU-AJ	4	74	LMB10UU-OP	3	57	5/8	15.875	15.875	0-0.0025	0/4	0-0.0060	0/9	1.1250/28.575	0-0.0050	0/13	1.5000/38.100	0-0.008	0/200	0-0.008	0/200	0.030/0.092	1.0590/26.899	0/41.5	3759/525	80°	0.003/8	0.005/12	-0.001/3	774	1180	
LMB12UU	5	95	LMB12UU-AJ	5	93	LMB12UU-OP	4	76	3/4	19.05	0.75	19.05	0-0.0030	0/7	0-0.0060	0/10	31.750/1.2500	0-0.0065	0/16	1.6250/41.275	0-0.008	0/200	0-0.008	0/200	0.030/0.092	1.1760/28.870	0/41.5	4375/11.1125	60°	0.004/10	0.006/15	-0.002/4	862	1370
LMB12UU	6	200	LMB12UU-AJ	6	198	LMB12UU-OP	5	170	1	25.4	1	25.4	0-0.0030	0/7	0-0.0060	0/10	39.688/1.5625	0-0.0065	0/16	2.2500/67.150	0-0.012	0/300	0-0.012	0/300	0.030/0.092	1.4687/37.306	0/41.5	5625/14.2875	50°	0.004/10	0.006/15	-0.002/4	980	1570
LMB20UU	6	440	LMB20UU-AJ	6	430	LMB20UU-OP	5	370	1.1/4	31.75	1.25	31.75	0-0.0035	0/8	0-0.0050	0/12	50.800/2.0000	0-0.0075	0/19	2.6250/66.675	0-0.012	0/300	0-0.012	0/300	0.030/0.092	1.8850/47.904	0/41.5	625/15.875	50°	0.005/12	0.008/20	-0.003/8	1570	2740
LMB24UU	6	670	LMB24UU-AJ	6	660	LMB24UU-OP	5	570	1.1/2	38.1	1.5	38.1	0-0.0035	0/8	0-0.0050	0/12	60.3125/3.750	0-0.0075	0/19	3.0000/76.200	0-0.012	0/300	0-0.012	0/300	0.030/0.092	2.2380/56.870	0/41.5	75/19.05	50°	0.005/12	0.008/20	-0.003/8	2180	4020
LMB32UU	6	1	LMB32UU-AJ	6	1120	LMB32UU-OP	5	980	2	50.8	2	50.8	0-0.0035	0/8	0-0.0050	0/12	76.200/5.0000	0-0.0090	0/22	4.0000/101.400	0-0.012	0/300	0-0.012	0/300	0.030/0.092	2.8370/72.085	0/41.5	1.0/25.40	50°	0.007/17	0.010/25	-0.005/13	3820	7940